

MF750T05

Macerating Toilet System



MACERATOR PUMP

FEATURES:

- 36 feet Max. Vertical Discharge
- 328 feet Max. Horizontal Discharge
- 4 Versatile Water Inlets
- 1½" Dual Use Vent Pipe
- Sewage Outlet With Built-in Check Valve

SPECIFICATIONS:

• Dimension: $17 \, {}^5/_{16}{}''L \, {}^* \, 11 \, {}^7/_{16}{}''H \, {}^* \, 7 \, {}^1/_{16}{}''W$

Power Factor: 0.85Insulation Class: 155(F)

• **Speed:** 3900 RPM

Power Consumption: 750 WSupply Voltage: 110V-60Hz

Enclosure Class: IP 55
Max. Flow: 150L/min
Start Level: 80mm
Stop Level: 30mm

• Cable Length: 39 3/8"

TWO-PIECE TOILET

FEATURES:

- Rear Discharge Two-Piece Toilet
- Chair-Height (16 1/2")
- Tornado Rimless Flushing
- 18 1/2" Comfortable Elongated Bowl
- Left-Handed Flush Lever

SPECIFICATIONS:

• N.W: 100.4 LB

Dimension: 27 ³/₈"L * 29 ¹/₂"H * 15 ³/₄"W

• Trap Type: P-trap

• Flush Type: Rimless Flush

• Flush Rate: 1.28GPF

Waste Outlet: Wall

Seat Shape: Elongated

Installation Type: Floor Mounted
 Quality Assurance: Limited 2-Year



PACKAGE INCLUDED:



Toilet Bowl



Floor Mounting Kit



Extension Pipes



Water Tank (Fill Valve And Flapper Kit Pre-installed)



Tank-To-Bowl Gasket



Flush Lever



Toilet Seat



Seat Mounting Kit



Macerator Pump




Pump Fittings




Adapter



	Pump	Bowl	Water Tank	Toilet Seat	Extension Pipes
Material	Stainless Steel, Polypropylene	Ceramic	Ceramic	Ceramic	Polypropylene
Color	White	White	White	White	White
Weight	14.3 LB	61.1 LB	31.3 LB	4.2 LB	2.3 LB






















ABOUT WATER INLETS:






PUMP FITTINGS:



EXTENSION PIPES:





WATER TANK CONNECTION KIT:

