

MF600T05

Macerating Toilet System



MACERATOR PUMP

FEATURES:

- 30 feet Max. Vertical Discharge
- 260 feet Max. Horizontal Discharge
- 3 Versatile Water Inlets
- 1½" Dual Use Vent Pipe
- Sewage Outlet With Built-in Check Valve

SPECIFICATIONS:

- Dimension: 17 ⁵/₁₆"L * 11 ⁷/₁₆"H * 7 ¹/₁₆"W
- Power Factor: 0.85
- Insulation Class: 155(F)
- **Speed:** 3450 RPM
- Power Consumption: 600 W
- **Supply Voltage:** 110V-60Hz
- Enclosure Class: IP 55
- **Max. Flow:** 130L/min
- Start Level: 65mm
- Stop Level: 35mm
- Cable Length: 39 3/8"

TWO-PIECE TOILET

FEATURES:

- Rear Discharge Two-Piece Toilet
- Chair-Height (16 1/2")
- Tornado Rimless Flushing
- 18 1/2" Comfortable Elongated Bowl
- Left-Handed Flush Lever

SPECIFICATIONS:

N.W: 100.4 LB

Dimension: 27 ³/₈"L * 29 ¹/₂"H * 15 ³/₄"W

• Trap Type: P-trap

• Flush Type: Rimless Flush

Flush Rate: 1.28GPF

Waste Outlet: Wall

Seat Shape: Elongated

Installation Type: Floor Mounted

• Quality Assurance: Limited 2-Year



PACKAGE INCLUDED:



Toilet Bowl



Floor Mounting Kit



Extension Pipes



Water Tank (Fill Valve And Flapper Kit Pre-installed)



Tank-To-Bowl Gasket



Flush Lever



Toilet Seat



Seat Mounting Kit



Macerator Pump




Pump Fittings




Adapter



	Pump	Bowl	Water Tank	Toilet Seat	Extension Pipes
Material	Stainless Steel, Polypropylene	Ceramic	Ceramic	Ceramic	Polypropylene
Color	White	White	White	White	White
Weight	14.3 LB	61.1 LB	31.3 LB	4.2 LB	2.3 LB















ABOUT WATER INLETS:






PUMP FITTINGS:



EXTENSION PIPES:






WATER TANK CONNECTION KIT:






ABOUT WATER INLETS:



PUMP FITTINGS:



MaceratingFlo reserves the right to make revisions without notice to product specifications and dimensions. Product dimensions may differ due to manufacturing variations. Responsibility for using outdated or canceled specifications is not assumed. For the most current Specification Sheet, go to www.maceratingflo.com.